





CaMate 48 Series LPC Selection Table









(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
1	3	5	5.8	33	CM48I8-2040	1	1	2
	4		6.4	31		1.5		
	5		7.1	28		2		
	6		7.8	25		3		
	7		8.6	23		3		
	8		9.4	21		4		
	3	10	10.4	19	CM48I8-1040	4.5	1	2
	4		10.8	18		4.5		
	5		11.2	18		4.5		
	6		11.7	17		4.5		
	7		12.2	16		5		
	8		12.8	16		5		
	3	15	15.3	13	CM48I8-1040	6	1	2
	4		15.5	13		6		
	5		15.8	13		6		
	6		16.2	12		6.5		
	7		16.6	12		6.5		
	8		17.0	12		6.5		
3	20	20.2	10	CM48I8-1040	7	1	2	





(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
1	4	20	20.4	10	CM4818-1040	7	1	2
	5		20.6	10		7		
	6		20.9	10		7		
	7		21.2	9		7		
	8	21.5	9	7				
	3	25	25.2	8	CM4818-1040	7	1	2
	4		25.3	8		7		
	5		25.5	8		7		
	6		25.7	8		7		
	7	26.0	8	7				
	8	26.2	8	7				
	3	30	30.1	7	CM4818-1040	7	1	2
	4		30.3	7		7		
	5		30.4	7		7		
	6		30.6	7		7		
	7	30.8	7	7				
	8	31.0	6	7				
	3	35	35.1	6	CM4818-1040	7	2	3
	4		35.2	6		7		
	5		35.4	6		7		
	6		35.5	6		7		
	7	35.7	6	7				
	8	35.9	6	7				
	3	40	40.1	5	CM4818-1040	7	2	3
	4		40.2	5		7		
	5		40.3	5		7		
	6		40.4	5		7		
	7	40.6	5	7				
	8	40.8	5	7				
	3	45	45.1	4	CM4818-1040	7	2	3
	4		45.2	4		7		
	5		45.3	4		7		
	6		45.4	4		7		
	7	45.5	4	7				
	8	45.7	4	7				
	3	50	50.1	4	CM4818-1040	7	2	3
	4		50.2	4		7		
	5		50.2	4		7		





(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
1	6	50	50.4	4	CM4818-1040	7	2	3
	7		50.5	4		7		
	8		50.6	4		7		
	3	55	55.1	4	CM4818-1040	7	2	3
	4		55.1	4		7		
	5		55.2	4		7		
	6		55.3	4		7		
	7		55.4	4		7		
	8	55.6	4	7				
	3	60	60.1	3	CM4818-1040	7	2	3
	4		60.1	3		7		
	5		60.2	3		7		
	6		60.3	3		7		
	7		60.4	3		7		
	8	60.5	3	7				
	3	65	65.1	3	CM4818-1040	7	2	3
	4		65.1	3		7		
	5		65.2	3		7		
	6		65.3	3		7		
	7		65.4	3		7		
	8	65.5	3	7				
	3	70	70.1	3	CM4818-1040	7	2	3
	4		70.1	3		7		
	5		70.2	3		7		
6	70.3		3	7				
7	70.3		3	7				
8	70.5	3	7					
2	3	10	10.4	37	CM4818-2040	0	1	2
	4		10.8	36		1		
	5		11.2	35		1.5		
	6		11.7	33		1.5		
	7		12.2	32		1.5		
	8		12.8	31		1.5		
	3		15	15.3		26		
4	15.5	25		3				
5	15.8	25		3				
6	16.2	24		3				
7	16.6	24	3					





(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
2	8	15	17.0	23	CM4818-2040	3	1	2
	3		20.2	20		4		
	4		20.4	19		4		
	5	20	20.6	19	CM4818-2040	4	1	2
	6		20.9	19		4		
	7		21.2	19		4		
	8		21.5	18		4		
	3		25.2	16		5		
	4		25.3	16		5		
	5	25	25.5	16	CM4818-1040	5	1	2
	6		25.7	16		5		
	7		26.0	15		6		
	8		26.2	15		6		
	3		30.1	13		6		
	4		30.3	13		6		
	5	30	30.4	13	CM4818-1040	6	1	2
	6		30.6	13		6		
	7		30.8	13		6		
	8		31.0	13		6		
	3		35.1	11		6.5		
	4		35.2	11		6.5		
	5	35	35.4	11	CM4818-1040	6.5	2	3
	6		35.5	11		6.5		
	7		35.7	11		6.5		
8		35.9	11		6.5			
3		40.1	10		7			
4		40.2	10		7			
5	40	40.3	10	CM4818-1040	7	2	3	
6		40.4	10		7			
7		40.6	10		7			
8		40.8	10		7			
3		45.1	9		7			
4		45.2	9		7			
5	45	45.3	9	CM4818-1040	7	2	3	
6		45.4	9		7			
7		45.5	9		7			
8		45.7	9		7			
3	50	50.1	8	CM4818-1040	7	2	3	



(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
2	4	50	50.2	8	CM4818-1040	7	2	3
	5		50.2	8		7		
	6		50.4	8		7		
	7		50.5	8		7		
	8		50.6	8		7		
	3		55.1	7		7		
	4		55.1	7		7		
	5		55.2	7		7		
	6	55	55.3	7	CM4818-1040	7	2	3
	7	55.4	7	7				
	8	55.6	7	7				
	3	60.1	7	7				
	4	60.1	7	7				
	5	60	60.2	7	CM4818-1040	7	2	3
	6	60.3	7	7				
	7	60.4	7	7				
	8	60.5	7	7				
	3	65.1	6	7				
	4	65.1	6	7				
	5	65	65.2	6	CM4818-1040	7	2	3
	6	65.3	6	7				
	7	65.4	6	7				
	8	65.5	6	7				
	3	70.1	6	7				
4	70.1	6	7					
5	70	70.2	6	CM4818-1040	7	2	3	
6	70.3	6	7					
7	70.3	6	7					
8	70.5	6	7					
3	3	15	15.3	38	CM4818-2040	0	2	3
	4		15.5	37		0.5		
	5		15.8	37		0.5		
	6		16.2	36		1		
	7		16.6	35		1		
	8		17.0	34		1		
	3	20.2	29	2				
	4	20	20.4	29	CM4818-2040	2	2	3
	5	20.6	29	2				



(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate					
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)				
3	6	20	20.9	28	CM4818-2040	2	2	3				
	7		21.2	28		2						
	8		21.5	27		3						
	3	25	25.2	24	CM4818-2040	3	2	3				
	4		25.3	23		4						
	5		25.5	23		4						
	6		25.7	23		4						
	7		26.0	23		4						
	8		26.2	23		4						
	3		30	30.1		20			CM4818-1040	4	2	3
	4			30.3		20				4		
	5	30.4		20	4							
	6	30.6		19	4.5							
	7	30.8		19	4.5							
	8	31.0		19	4.5							
	3	35		35.1	17	CM4818-1040	4.5	2		3		
	4			35.2	17		4.5					
	5		35.4	17	4.5							
	6		35.5	17	4.5							
	7		35.7	17	4.5							
	8		35.9	17	4.5							
	3		40	40.1	15		CM4818-1040		6		2	3
	4			40.2	15				6			
	5	40.3		15	6							
	6	40.4		15	6							
	7	40.6		15	6							
	8	40.8		15	6							
	3	45		45.1	13	CM4818-1040		6	2	3		
	4			45.2	13			6				
	5		45.3	13	6							
	6		45.4	13	6							
	7		45.5	13	6							
	8		45.7	13	6							
	3		50	50.1	12		CM4818-1040	6.5			2	3
	4			50.2	12			6.5				
	5	50.2		12	6.5							
	6	50.4		12	6.5							
	7	50.5		12	6.5							



(M) No. of Lanes (Lane width: 3.5 m)	(X) Installation Height	(Y) Horizontal Distance to Target	(Z) Distance from Camera to Target	(HFOV) Field of View	CaMate Model	Rotating circle times (with an allen wrench)	No. of CaMate	
							Speed ≤90km/hr (Shutter ≤ 1/800)	90 ≤ Speed ≤ 120km/hr (Shutter ≤ 1/1000)
3	8	50	50.6	12	CM4818-1040	6.5	2	3
	3		55.1	11		6.5		
	4		55.1	11		6.5		
	5	55	55.2	11	CM4818-1040	6.5	2	3
	6		55.3	11		6.5		
	7		55.4	11		6.5		
	8		55.6	11		6.5		
	3		60.1	10		7		
	4		60.1	10		7		
	5	60	60.2	10	CM4818-1040	7	2	3
	6		60.3	10		7		
	7		60.4	10		7		
	8		60.5	10		7		
	3		65.1	9		7		
	4		65.1	9		7		
	5	65	65.2	9	CM4818-1040	7	2	3
	6		65.3	9		7		
	7		65.4	9		7		
	8		65.5	9		7		
	3		70.1	9		7		
	4		70.1	9		7		
	5	70	70.2	9	CM4818-1040	7	2	3
	6		70.3	9		7		
	7		70.3	9		7		
8		70.5	9		7			