



S SD9365-EHL Kit

H.265 IR PTZ Dome &
Outdoor PoE Injector

1080p 60 fps • 20x Zoom • 150M IR • IP66 • IK10 •
NEMA 4X • -50°C ~ 55°C • Wiper

The SD9365-EHL is the latest professional speed dome camera with wiper from VIVOTEK, specifically designed to enhance low light surveillance in large coverage areas. Equipped with 150 M IR illuminators and a 20x optical zoom lens, the SD9365-EHL provides a superb low light image in the most challenging situations. The SD9365-EHL also adopts VIVOTEK's latest IR technology, VAIR (Vari-Angle IR). VIVOTEK's VAIR provides smooth vari-angle adjustment of the IR illuminators, allowing broad coverage FOV and highly uniform IR intensity while avoiding hot-spots traditionally associated with IR illumination.

The SD9365-EHL is the PTZ surveillance camera with IR Illumination to utilize H.265 compression technology. When combined with VIVOTEK's Smart Stream II technology users can obtain bandwidth savings of up to 80%* compared to traditional H.264. By combining 1080p full HD resolution with H.265, IR illuminators, VAIR, WDR, and 20x optical zoom, the SD9365-EHL is able to capture fine details at top-notch quality, 24 hours a day, 7 days a week.

VIVOTEK further strengthened the camera performance with an IP66- and NEMA 4X-rated housing to protect the camera against rain, dust, and corrosion. The SD9365-EHL has a wide operating temperature range from -50°C to 55°C, ensuring continuous operation under the most extreme weather conditions and hazardous environments. This makes the SD9365-EHL ideally suited to monitor wide open spaces such as ports, highways, cities, and parking lots where high-level precision is required.

VIVOTEK's SD9365-EHL is now available in a bundle kit that includes outdoor PoE injector AP-GIC-015B-095, a 95W outdoor-ready unit designed with a weatherproof IP67 and vandal-proof IK10 rated housing. This outdoor bundle helps users to reduce installation time and hardware costs.

* Depending on scene.

Key Features

- Real-time H.265, H.264 and MJPEG Compression (Triple Codec)
- 60 fps @ 1080p Full HD
- 20x Zoom Lens
- 150M IR with VAIR (Vari-Angle IR)
- WDR Pro for Unparalleled Visibility in High Contrast Environments
- Weather-proof IP66, Vandal-proof IK10 and NEMA 4X-rated Housing
- -50°C ~ 55°C Wide Temperature Range for Extreme Weather Conditions (AC 24V/ PoH)
- Smart Stream II to Optimize Bandwidth Efficiency
- EIS
- Easy Cleaning with Built-in Wiper




Without VAIR



With VAIR

Application



Ordering Information

Outdoor PoE Injector Solution	P/N.	IP Camera	Outdoor PoE injector
	199003000G	 SD9365-EHL 20x, 1080P, IR Speed Dome, 150M IR, IP66, IK10	 AP-GIC-015B-095 Outdoor 95W PoE injector with adapter, IP67, IK10

Technical Specifications

Model	SD9365-EHL	Minimum Illumination	0.26 Lux @ F1.6 (Color) 0.01 Lux @ F1.6 (B/W) 0 Lux with IR illumination on
System Information		Pan Speed	0.1° ~ 300° / sec
CPU	Multimedia SoC (System-on-Chip)	Pan Range	360° endless
Flash	128MB	Tilt Speed	0.1° ~ 300° / sec
RAM	512MB	Tilt Range	220° (-110° ~ +110°)
Camera Features		Preset Locations	256 preset locations 128 presets per tour
Image Sensor	1/3" Progressive CMOS	Pan/Tilt/Zoom Functionalities	128x digital zoom (4x on IE plug-in, 32x built-in), Auto pan mode, Auto patrol mode
Max. Resolution	1920x1080	On-board Storage	Slot type: Micro SD/SDHC/SDXC card slot Seamless Recording
Lens Type	20x Optical Zoom, Auto Focus	Video	
Focal Length	f = 4.7 ~ 94 mm (20x zoom)	Compression	H265, H264, MJPEG
Aperture	F1.6 ~ F3.5	Maximum Frame Rate	H.265 & H.264: 60 fps @ 1920x1080 MJPEG: 30 fps @ 1920x1080
Iris type	DC-Iris	Maximum Streams	4 simultaneous streams
Field of View	3° ~ 55° (Horizontal) 2° ~ 33° (Vertical) 3° ~ 63° (Diagonal)	S/N Ratio	53 dB
Shutter Time	1/8 sec. to 1/30,000 sec.	Dynamic Range	110 dB
WDR Technology	WDR Pro	Video Streaming	Adjustable resolution, quality and bitrate Smart Stream II
Day/Night	Yes		
Removable IR-cut filter	Yes		
IR Illuminators	Built-in IR Illuminators up to 150 meters with VAIR IR LED*2		

Technical Specifications

Image Settings	Adjustable image size, quality and bit rate; Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks (Up to 24); Scheduled profile settings, defog, 3DNR, EIS, HLC
Audio	
Audio Capability	Two-way Audio
Compression	G.711, G.726
Interface	External microphone input External line output
Network	
Users	Live viewing for up to 10 clients
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/ RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, TLS, NTCIP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Supported, specification available at www.onvif.org
Intelligent Video	
Video Motion Detection	Five-window video motion detection
Auto-Tracking	Auto-tracking on moving object
Alarm and Event	
Alarm Triggers	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
Alarm Events	Event notification using digital output, HTTP, SMTP, FTP, NAS server and Micro SD card File upload via HTTP, SMTP, FTP, NAS server and Micro SD card
General	
Connectors	RJ-45 cable connector for Network 10/100 Mbps PoE connection*1 Audio input*1 Audio output*1 AC/DC 24V power input*1 Digital input*4 Digital output*2 RS-485 for PTZ control (PelcoD protocol, Baud rate 2400)*1
LED Indicator	System power and status indicator

Technical Specifications

Model	AP-GIC-015B-095
PoE Function	
Max. PoE Output Power/ per Port	54VDC/95W
Power Pin Assignment	1/2(-), 3/6(+), 4/5(+), 7/8(-)

Power Input	PoH/PoE (95W) AC/DC 24V
Power Consumption	PoH/PoE (95W): Max. 70 W (Heater on) Max. 51 W (Heater off) AC/DC 24V: Max. 63 W (Heater on) Max. 45 W (Heater off)
Dimensions	236.45 x 364.2 mm
Weight	5,700 g
Casing	IP66, IK10, NEMA 4X
Safety Certifications	CE, FCC Class A, VCCI, C-Tick, NEMA 4X, UL
Operating Temperature	Starting Temperature: -40°C ~ 55°C (-40°F ~ 131°F) Working Temperature: -40°C ~ 55°C (-40°F ~ 131°F), DC 24V power input -50°C ~ 55°C (-58°F ~ 131°F), AC 24V/ PoH(95W) power input *Wiper is functional at 10°C to 55°C (50°F to 131°F)
Humidity	98%
Warranty	36 months


System Requirements

Operating System	Microsoft Windows 8/7
Web Browser	Mozilla Firefox 7~43 (streaming only) Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above Quicktime: 7 or above

Included Accessories

CD	User's manual, quick installation guide, Shepherd, VAST
Others	Wall mount bracket, screws, waterproof connectors, terminal blocks, quick installation guide, warranty card, alignment sticker, ground wire, T25 star driver, software CD, desiccant bags, I/O cable

Dimensions




General

Power Input	100~240VAC / 50~60Hz
Power Consumption	100W
Surge Protection Data/ PoE port	12 KV

Technical Specifications

Surge Protection AC Power	10 KV
Waterproof	IP67
Vandal Proof	IK10
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)

Dimensions



Compatible Accessories

Others



AJ-001
USB Joystick



AJ-002
USB Joystick