

EN50155 Compliant Product Offerings


| | Network Cameras | | | | |
|-------------------|--|---|--|--|--|
| |  MD8531H |  MD8562/62D |  MD8563-EH |  FE8174V |  FE8181V |
| Frame per Second | 30 fps @ 1280x960 | 30 fps @ 1920x1080 | 30 fps @ 1920x1080 | 15 fps @ 1920x1920 30 fps @ 1920x1080 | 15 fps @ 1920x1920 30 fps @ 1920x1080 |
| IR Illuminators | - | - | - | - | 10 m IR |
| Video Compression | H.264, MJPEG & MPEG-4 | H.264, MJPEG & MPEG-4 | H.264 & MJPEG | H.264, MJPEG & MPEG-4 | H.264, MJPEG & MPEG-4 |
| Audio Capability | Two-way Audio | Audio In | Two-way Audio | Two-way Audio | Two-way Audio |
| 3DNR | v | - | v | - | v |
| WDR | WDR Pro | WDR Enhanced | WDR Pro | WDR Enhanced | WDR Enhanced |
| Housing | IP66, IK10 | IP67, IK10 | IP67, IK10 | IP66, IK10 | IP66, IK10 |
| Power Input | PoE | PoE (MD8562) DC 12V (MD8562D) | PoE | PoE DC 12V | PoE Plus DC 12V |
| Connectors | RJ45, M12 (Optional) | RJ45, M12 (Optional) | M12 | RJ45 | RJ45 |
| Dimensions | 129 (D) x 107 (W) x 54 (H) mm | 130 (D) x 107 (W) x 47 (H) mm | 129 (D) x 107 (W) x 54 (H) mm | Ø 145 x 47 mm | Ø 160 x 51 mm |

| | Industrial PoE Switches | | |
|---|--|--|--|
| |  AW-IHT-0600 |  AW-IHT-0601 |  AW-IHT-0602 |
| Short Highlight | Industrial 4xGE PoE + 1xGE Combo + 1xGE SFP Switch | Industrial 4xGE PoE + 1xGE Combo + 1xGE SFP Switch | Industrial 4xFE M12 PoE + 2xFE M12 Switch |
| Fast Ethernet 10/100Mbps (M12) | - | - | 6 |
| Gigabit Ethernet 10/100/1000Mbps (RJ45) | 5 | 5 | - |
| Gigabit Ethernet 100/1000Mbps (SFP) | 2 | 2 | - |
| Number of PoE Out Ports | 4 | 4 | 4 |
| Max. PoE Output Power/ per Port | 30 W | 30 W | 30 W |
| Power Input | Redundant Dual 44V-56V DC Power Input Removable Terminal Block | Redundant Dual 12V-56V DC Power Input Removable Terminal Block | Redundant Dual 24V-56V DC Power Input M12 Connect |
| Operating Temperature | -40°C ~ 75°C (-40°F ~ 167°F) | -40°C ~ 75°C (-40°F ~ 167°F) | -40°C ~ 75°C (-40°F ~ 167°F) |
| Dimensions | 142 (L) x 105 (W) x 43 (H) mm | 142 (L) x 105 (W) x 43 (H) mm | 100 (L) x 150 (W) x 85 (H) mm |



Transport, a Part of Life that Needs Security

Transportation is a vital part of everyday life for the modern individual. As the use of mass transportation increases, so does the need for comprehensive surveillance systems that ensure the safety of passengers and increase overall efficiency. VIVOTEK offers ideal solutions that are compliant with industrial standards, such as EN50155, for railway applications.





EN50155

VIVOTEK Provides Dedicated Solutions for Railway Systems

The variety of environments and conditions encompassed by the railway sector is vast—outdoor and indoor spaces; wide-open and constrained areas; low-light and brightly lit; day and night – railways cover every conceivable operating environment. In view of this situation, VIVOTEK has developed a broad range of solutions, including high-performance network cameras and industrial switches. All of devices are compliant with the EN50155 standard.



Front and Rear Facing



MD8563-EH

- 30 fps @ 1920x1080
- WDR Pro
- Video Rotation
- Two-way Audio




Pantograph



MD8531H

- 30 fps @ 1280x960
- WDR Pro 120dB
- Vandal-proof IK10 Housing
- Weather-proof IP66 Housing



Driver Car



Industrial M12 PoE Switch

- 4xFE PoE M12 + 2xFE M12 Ports
- Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F)
- Redundant 24~56VDC Power Input for Backup
- 24VDC/1A Alarm Relay Output
- Compact Size



FE8181V

- 5 MP CMOS Sensor
- 360° Surround View
- 10M IR
- Compact Size



Carriage Exterior



MD8531H

- 30 fps @ 1280x960
- WDR Pro 120dB
- Video Rotation
- Vandal-proof IK10 Housing
- Weather-proof IP66 Housing



MD8563-EH

- 30 fps @ 1920x1080
- WDR Pro
- Video Rotation
- Two-way Audio
- Vandal-proof IK10 Housing
- Weather-proof IP67 Housing



MD8562/62D

- 30 fps @ 1920x1080
- FOV: 110° (H), 82° (V)
- Video Rotation
- Vandal-proof IK10 Housing
- Weather-proof IP67 Housing



Carriage Interior



MD8562/62D

- 30 fps @ 1920x1080
- FOV: 110° (H), 82° (V)
- Video Rotation
- One-way Audio
- Compact Size
- Vandal-proof IK10 Housing
- Tampering Detection



FE8174V/FE8181V

- 5 MP CMOS Sensor
- 180° Panoramic View
- 360° Surround View
- 10M IR (FE8181V)
- Compact Size
- Two-way Audio
- Vandal-proof IK10 Housing
- Tampering Detection