



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Series	Model	Description
Box Cameras	SUPREME	IP9164-HT(NON-LENS)	NDAA, Box Camera, 2M 60fps, H.265/H.264/MJPEG, w/o lens, DC/P-iris/i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio.
	SUPREME	IP9164-LPC	NDAA, License plate capture, Box Camera, 2M 60fps, H.265/H.264/MJPEG, DC-iris/P-iris/i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9165-HT-v2	Box Camera, 2M 60fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9165-LPC-v2	License plate capture, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9165-LPR-v2 Kit (Street)	License plate recognition kit, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, manual focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, Snap-in IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
	V-Series	IP9181-HT-v2	Box Camera, 5M 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	V-Series	IP9181-LPC-v2	License plate capture, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	V-Series	IP9181-LPC-v2 (Kit)	License plate capture kit, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, External IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
	SUPREME	IP9191-HT-v2	Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9191-LPC-v2	License Plate Capture, Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
Bullet Cameras	SUPREME	IB9365-EHT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~60° C (-58° F ~ 140° F)
	SUPREME	IB9365-HT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	SUPREME	IB9365-HT-A(12-40MM)	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f12 ~ 40mm Motorized Lens, P-iris, IR 100m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	SUPREME	IB9365-EHT-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	V-Series	IB9367-EHT-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	IB9367-EHT-v2 (5-50mm)	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	C-Series	IB9368-HT	Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IB9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm or 3.6mm, IR 30m, Smart motion, PoE/DC12V, Working Temperature: -30° C ~ 50° C (-22° F ~ 122° F)
	C-Series	IB9380-H	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IB9387-EHT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	V-Series	IB9387-HT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IB9388-HT	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IB9389-EH-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	IB9389-EHT-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Series	Model	Description
Bullet Cameras	SUPREME	IB9391-EHT-v2	Outdoor Vandal-proof Bullet, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
	V-Series	IB9387-LPR-v2	License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/ AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
Fixed Dome Cameras	SUPREME	FD9165-HT-A	Indoor Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 45° C (14° F ~ 113° F)
	C-Series	FD9166-HN(2.8MM)	Indoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
	C-Series	FD9166-HN(3.6MM)	Indoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
	V-Series	FD9167-HT-v2	Indoor Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~50°C (14°F ~ 122°F)
	C-Series	FD9182-H	Recessed design dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/ N, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C~ 50°C (-10°F ~ 122°F)
	V-Series	FD9187-HT-A	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 45° C (14° F ~ 113° F)
	SUPREME	FD9365-EHTV-A	Outdoor Vandal Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	SUPREME	FD9365-HTV-A	Outdoor Vandal Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	SUPREME	FD9365-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
	C-Series	FD9366-HV(2.8MM)	Outdoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
	C-Series	FD9366-HV(3.6MM)	Outdoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
	V-Series	FD9367-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
	C-Series	FD9368-HTV	Outdoor Vandal Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm, IR 30m, Smart motion, PoE/DC12V, Built in Mic, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
	C-Series	FD9380-H	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9380-H(2.8MM)	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	FD9387-EHTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~60° C (-58° F ~ 140° F)
	V-Series	FD9387-HTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9388-HTV	Outdoor Vandal Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	FD9189-H-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
V-Series	FD9189-HT-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)	



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Series	Model	Description
	V-Series	FD9389-EHV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature:-40°C ~ 60°C (-40°F ~ 140°F)
	V-Series	FD9389-EHTV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
	SUPREME	FD9391-EHTV-v2	Outdoor Vandal-proof Dome, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-Iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, Smart IR III, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
	INSIGHT	FD9392-EHTV-O	8MP, 50M IR, Edge AI, Driven by OSSA, Azena OS, IP67, IK10
	SUPREME	CD9381-HNTV	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.8~8mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F)
	SUPREME	CD9381-HNVF2	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.4mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F)
	C-Series	IT9360-H	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9360-H(2.8MM)	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9380-H	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9380-H(2.8MM)	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9388-HT	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IT9389-H-v2	Turret Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature:-20°C ~ 50°C (-4°F ~ 122°F)
180° Cameras	C-Series	CC9160-H	Indoor, 2M 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.66mm,fisheye lens, Daytime, PoE, built-in mic, DI/DO, operating temp (0°F ~ 40°C)
	C-Series	CC9160-H(HS)	Indoor, 2M 180° Panoramic height strip(feet, cm), 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (0°F ~ 40°F)
	C-Series	CC9380-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
	C-Series	CC9381-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
	V-Series	MS9390-HV-v2	Outdoor Vandal Dome, 8MP 180° Panoramic (2x4M sensors), 30fps, H.265/H.264/MJPEG, f2.8mm lenses, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-40° C ~55° C/ -40°F ~ 131°F)
360° Cameras	C-Series	FE9180-H-v2	Indoor, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, daytime only, WDR Pro, PoE, Built-in Mic, MicroSD/SDHC/SDXC
	SUPREME	FE9192-H	Recessed Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC
	C-Series	FE9380-HV	Outdoor Vandal Proof, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, D/N, IR 10m, WDR Pro, 3DNR, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp -30°C ~ 60°C / -22 °F ~ 140 °F
	SUPREME	FE9382-EHV-v2	Outdoor Vandal Proof, 6M, 30fps, H.265/H.264/MJPEG, f1.245mm lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 55°C / -40 °F ~ 131 °F), DI/DO/ Audio Cable available by special order (PRR)
	SUPREME	FE9191-H-v2	Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC
	SUPREME	FE9391-EHV-v2	Outdoor Vandal Proof, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 60°C / -40 °F ~ 140 °F), DI/DO/ Audio Cable available by special order (PRR)
Multi-Sensor Cameras	SUPREME	MA9322-EHTVL	Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.7~7.7mm motorized lenses, D/N, WDR Pro 120dB, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 50°C/ - 40°F ~ 122°F)



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Series	Model	Description
Mobile Dome Cameras	SUPREME	MD8564-EH	Mobile Dome, 2M 30fps, H.264/MJPEG, f3.6mm fixed Lens, IR 15M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IP68, IK10, NEMA 4X, EN50155 TX
	V-Series	MD9560-DH(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	V-Series	MD9560-H(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	V-Series	MD9560-H(3.6MM,HL1)	Mobile Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	SUPREME	MD9582-H	Mobile Dome, 5M 30fps, H.265, f2.8mm or 3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built-in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT4, EN45545 HL1 or HL3
	SUPREME	MD9584-H	Mobile Dome, 5M 30fps, H.265, f3.6mm fixed Lens, 850nm IR 50M, WDR Pro, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IK68, IK10+, NEMA 4X, EN50155 OT4, EN45545 HL3
Speed Dome Cameras	SUPREME	SD9161-H-v2	Indoor Speed Dome, 2M 30fps, H.265/H.264/MJPEG, 10x Optical Zoom, WDR Pro, 3DNR, PoE/AC 24V/DC 48V, I/O*2/1, Two way audio, MicroSD/SDHC/SDXC
	SUPREME	SD9384-EHL	IR Speed Dome, 5M 30fps, H.265, 30x Optical Zoom, IR 200M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
	SUPREME	SD9368-EHL	IR Speed Dome, 2M 60fps, H.265, 40x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
AI Counting Cameras	SUPREME	SC8131	Stereo People Counting Network Camera, dual image sensors, lens f = 2mm, H.264/MJPEG, Starting Temperature: 0°C ~ 40°C (32°F ~ 104°F), Working Temperature: -10°C ~ 40°C (14°F ~ 104°F), Installation Height: 240~500 cm (7.9~16.4')
	SUPREME	SC8132	Stereo People Counting Network Camera, dual image sensors, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240 cm (6.2~7.9')
	SUPREME	SC8133	Stereo People Counting Network Camera, dual image sensors, white LED, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240cm (6.2~7.9')
	SUPREME	SC9133	Deep Learning AI Counting Network Camera, Deep Learning AI Detection* for Passenger Classification, White LEDs for Low Lighting Counting, EN50155
	SUPREME	SC9133-RTL	AI Counting Network Camera for Retail, Deep Learning AI Counting, 140° Fiseye FOV for Better Coverage, Flexible Installation Height 2.4 to 10 m
Split-type Camera System	V-Series	VC9101	Video Core, split-type, H.265,H.264/MJPEG, PoE/DC 8-36V, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, operating temp(-10°C ~ 50°C); work with camera unit (CU series)
Video Server	C-Series	VS8100-v2	Video server, 1CH, D1 30pfs, H.264, MJPEG, DC 12V, One-way Audio
Facial Recognition Solutions	Tablet	FT9361-R	Facial Recognition Access Control Tablet, Linux OS, Memory: 8GB ROM 1GB RAM, Max. 50,000 profiles, 1080P camera, 1440x720 display, PoE Class 4/DC 12V, Weigand
AI Box	INSIGHT	IE9111-O	NDAA, AI-Box, Edge AI Device, Driven by OSSA, Azena OS, VCA
	INSIGHT	IE9111-O (M12)	NDAA, AI-Box, Edge AI Device, Driven by OSSA, Azena OS, VCA, M12 Connection
NVRs	C-Series	ND9213P	H.265, 4CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 4/2 alarm in/out, 1HDD, 1 LAN(FE), 4 PoE, NDAA
	V-Series	ND9323P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 8 PoE
	V-Series	ND9425P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE
	V-Series	ND9442P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
	V-Series	ND9542P	H.265, 32CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
	SUPREME	NR9581-v2	H.265, 32CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
	SUPREME	NR9681-v2	H.265, 64CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
	SUPREME	NR9682-v2	H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot- swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
	SUPREME	NR9782-v2	H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
	SUPREME	NS9521	H.265, 32CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 2 HDD, 2 LAN(Giga), VAST2 Station



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
PoE	EPoC	AM-713-E_V01	Conduit box with EPoC Tx module for Outdoor fixed dome
	EPoC	AP-FEX-0100-R	EPoC PoE in Rx Module, 1x BNC, 1x FE RJ45, -20 ° C~60 ° C
	EPoC	AP-FEX-0105-D,USA	EPoC Extender DC kit, AP-FEX-0105-R + AP-FEX-0105-T + AA-420, USA
	EPoC	AP-FEX-0105-P	EPoC Extender PoE kit, AP-FEX-0100-R + AP-FEX-0105-T
	EPoC	AP-FEX-0105-R,USA	EPoC DC in Rx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C, AA- 420, USA
	EPoC	AP-FEX-0105-T	EPoC DC in Tx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C
	EPoC	AP-FEX-0150-T	EPoC Outdoor Tx Module, 1x BNC, 1x FE RJ45, -40 ° C~60 ° C, IP67, IK10
	EPoC	AP-FEX-0200-T	EPoC Tx Module, 1x BNC, 2x FE RJ45, -20 ° C~60 ° C
	EPoC	AP-FEX-0250-T	EPoC Outdoor Tx Module, 1x BNC, 2x FE RJ45, -40 ° C~60 ° C, IP67, IK10
	EPoC	AT-BSP-001	Coax surge protector for EPoC modules
	EPoC	AW-FCT-050A-250,USA	4xFE BNC + 1x GE RJ45 unmanaged EPoC switch, USA
	Extender	AP-FXC-0110	1-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C
	Extender	AP-FXC-0160	1-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
	Extender	AP-FXC-0210	2-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C
	Extender	AP-FXC-0260	2-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
	Extender	AP-GXC-0150	1-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
	Extender	AP-GXC-0250	2-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C
	Extender	AP-FXC-0400	4-Port indoor FE PoE Extender
	Hyper PoE Extender	AP-FHP-0100-R	Hyper PoE PoE in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C
	Hyper PoE Extender	AP-FHP-0105-R,USA	Hyper PoE DC in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C AA-420, US power cord
	Hyper PoE Extender	AP-FHP-0105-T	Hyper PoE Tx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C
	Industrial Solution	AW-IHH-0800	Industrial 4xGE 95W POH/PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 95W, Power budget 240W, 54~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-0800	Industrial 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 120W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-1000	Industrial 8xGE PoE + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 240W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-1271	Industrial VivoCam L2+ Managed PoE Switch 8xGE PoE + 4xGE SFP Per PoE port Max. 30W, power budget 240W, 48~57VDC input, - 40° C to 75° C
	Industrial Solution	AW-IHH-0110	Industrial Gigabit 95W POH/POE Injector Industrial Gigabit 95W POH Injector, 48-56VDC input, -40° C to +75° C
	Industrial Solution	AW-IHS-0202	Industrial Media Convert SFP True Mini Industrial Media Converter, 10/100M RJ45 to 100M SFP, Designed for outdoor CAM enclosure, Din-Rail mount and Panel mount, 18-36VAC/12- 60VDC, -40° C to 75° C
	Industrial Solution	AW-IHT-0100	Industrial Gigabit 30W POE Injector Industrial Gigabit 30W POE Injector, 48-56VDC input, -40° C to +75° C
	Industrial Solution	AW-IHT-0200	Industrial 1xGE PoE + 1xGE SFP Switch 1 port 802.3at 30W POE 10/100/1000M + 1 port 100/1000M SFP, 48~56VDC inp ut, -40° C to 75° C



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022


Category	Form Factor	Model	Description
PoE	Industrial Solution	AW-IHH-0410	Industrial 2xGE 95W POH/POE + 2xGE SFP Switch, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-0601	Industrial 4XGE POE+2XGE SWITCH SFP 12V-56V Super Voltage Booster 12~56VDC input, 4 port 802.3at 30W POE 10/100/1000M + 1 port 10/100/1000M SFP/TX Combo + 1 port 100/1000M SFP, -40° C to 75° C
	Industrial Solution	AW-IHT-0602	Industrial EN50155 4xFE M12 PoE + 2xFE M12 Switch 4 port 802.3at 30W POE M12 10/100M + 1 port M12 10/100M, 24~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHB-0100	Industrial Gigabit 802.3bt 90W PoE injector, 48-56VDC input, -40° C to +75° C
	Industrial Solution	AW-IHB-0400	Industrial 2xGE 802.3bt 90W PoE + 2xGE SFP Switch, power budget 180W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHB-0800	Industrial 4xGE 802.3bt 90W PoE + 2xGE UTP + 2xGE SFP Switch, power budget 360W, 54~56VDC input, -40° C to 75° C
	Injector	AP-FIC-010A-015,USA	Indoor IEEE802.3af FE PoE Injector
	Injector	AP-GIC-010A-030,USA	Indoor IEEE802.3at Gigabit PoE Injector
	Injector	AP-GIC-011A-060,USA	Indoor Gigabit PoH 60W Injector
	Injector	AP-GIC-011A-095,USA	Indoor Gigabit PoH 95W Injector
	Injector	AP-GIC-015B-095	outdoor Gigabit PoH 95W Injector
	Managed Switch	AW-GEV-104B-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 130W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-107A-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 130W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-184B-250,USA	16-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 250W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-264B-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 370W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-267A-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 370W) Integrate with Vivotek Camera for surveillance application
	Managed Switch	AW-GTS-287A,USA	24xGE SFP + 4xCombo GE + 4x 10G SFP+ L2 Plus Managed Switch
	Optical Transceiver	SFP-1000-CPTX-X1	Gigabit SFP to RJ45 Module
	Optical Transceiver	SFP-1000-CPTX-X1I	Industrial Gigabit SFP to RJ45 Module
	Optical Transceiver	SFP-1000-MM13-02	Gigabit Mini GBIC Multi Mode 1310nm 2KM, LC Connector
Optical Transceiver	SFP-1000-MM13-02I	Industrial Gigabit Mini GBIC Multi Mode 1312nm 2KM, LC Connector	
Optical Transceiver	SFP-1000-MM85-X5	Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector	



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
PoE	Optical Transceiver	SFP-1000-MM85-X5I	Industrial Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-10	Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-10I	Industrial Gigabit Mini GBIC Single Mode 1312nm 10KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-40	Gigabit Mini GBIC Single Mode 1310nm 40KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-40I	Industrial Gigabit Mini GBIC Single Mode 1312nm 40KM, LC Connector
	Optical Transceiver	SFP-2000-MM85-X3	10 Gigabit Mini GBIC Multi Mode 850nm 0.3KM, LC Connector
	Optical Transceiver	SFP-2000-SM13-10	10 Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
	Outdoor Cabinet	AT-CAB-001	Cabinet IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism. Mounting bracket for wall, DIN- rail, cover is included.
	Outdoor Cabinet	AT-CAB-002	Side-mount bracket for HLG series power supply Protects accessory devices such as 120W power supply.
	Outdoor Cabinet	AT-CAS-001	Cabinet for Speed dome IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism. Mounting bracket for wall, DIN- rail, cover
	Outdoor Cabinet	AT-DRB-001	Cabinet industrial 95W PoE switch AW-IHH-0800 bracket
	Outdoor Cabinet	AT-PSP-001	PoE Surge Protector: 8-10KA AT-PSP-001 is a surge protection device to provide Signal/Power path and surge protection capability. It employed our patented surge blocker with shunt devices and parallel devices to guarantee the safety of your device, ev
	Outdoor Cabinet	AT-SUN-001	Sunshield for AT-CAx series cabinet Metal sunshield for Vivotek Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation.
	Outdoor Cabinet	AT-SUN-002	Sunshield for AT-CAx + AT-CAB-002 cabinet Metal sunshield for BOTH Vivotek Cabinet and DC Power cabinet. Reduces the temperature inside the cabinet, caused by sun radiation.
	Outdoor Cabinet	AT-SWH-000	Power Safety Kit (100~275VAC): 20-40KA Electrical safety kit for Vivotek Cabinet in countries where the mains power is 275V AC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.
	Outdoor Cabinet	AT-SWH-002	Door open/close detection switch Intrusion door switch for Vivotek Cabinet, connection to I/O port.
	Outdoor Cabinet	AT-WPC-001	Cable gland M16 CABLE GLAND 4~7mm AWG 6PCS
	Outdoor Cabinet	AT-WPC-002	Cable gland M16 CABLE GLAND for Corrugated Tubing : 5/16 " 6PCS
	Outdoor Surger	AP-PSP-050	Outdoor PoE Surge Protector 16KV surge Operating temperature from -40° C to 85° C
	Outdoor Switch	AW-GEH-043A-120	Outdoor Unmanaged 2xGE 95W PoH/PoE + 2xGE SFP Switch, Per PoE port max. 95W, power budget 120W, IP67, IK10
Outdoor Switch	AW-GET-083A-120	Outdoor Unmanaged 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port max. 30W, power budget 120W, IP67, IK10	
Outdoor Switch	AW-GEU-086A-240	Outdoor VivoCam L2+ Managed 4xGE UPoE + 2xGE UTP + 2xGE SFP Switch, Per PoE Port max. 60W, power budget 240W, IP67, IK10	



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
PoE	Power Supply	HLG-120H-24	90~305VAC In ,24VDC/120Wut ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-120H-48	90~305VAC In ,48VDC/120W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-120H-54	90~305VAC In ,54VDC/120W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-240H-54	90~305VAC In ,54VDC/240W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-60H-24	90~305VAC In ,24VDC/60Wut ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-24	90~305VAC In ,24VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-48	90~305VAC In ,48VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-54	90~305VAC In ,54VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	NDR-120-48	90~264VAC In, 48VDC/120W Out , - 20 °C ~ 70 °C
	Power Supply	NDR-240-48	90~264VAC In, 48VDC/240W Out , - 20 °C ~ 70 °C
	Power Supply	NDR-75-48	90~264VAC In, 48VDC/75W Out , - 20 °C ~ 70 °C
	Power Supply	DRL-48V120W1EN	90~264VAC In, 48VDC/120W Out , - 30 °C ~ 70 °C
	Power Supply	DRL-48V240W1EN	90~264VAC In, 48VDC/240W Out , - 30 °C ~ 70 °C
	Unmanaged Switch	AW-FET-060C-065,USA	4xFE POE +2FE UTP Switch, USA
	Unmanaged Switch	AW-FGT-100D-120	8xFE PoE + 2xGE Combo Switch
	Unmanaged Switch	AW-FGT-180D-250,USA	16xFE POE +2G COMBO Switch, USA
	Unmanaged Switch	AW-FGT-260D-380,USA	24xFE POE +2G COMBO Switch, USA
	Unmanaged Switch	AW-GET-050A-065,USA	4xGE POE + 1xGE SWITCH
	Unmanaged Switch	AW-GET-100A-120,USA	8XGE POE + 2XG SFP SWITCH





# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
Accessory	Enclosure	AE-238	Side Open Aluminum Camera Housing AC24V in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
	Enclosure	AE-239	Side Open Aluminum Camera Housing PoE in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
	Enclosure	AE-243	Side Open Aluminum Camera Housing, AC24V in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
	Enclosure	AE-244	Side Open Aluminum Camera Housing, PoE in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
	Enclosure	AE-23A	Side Open Aluminum Camera Housing AC24V in,Window heater, Fan,IP68, -20~50°C , optional snap-in VAIR,Wall bracket, Sun shield
	Enclosure	AE-23E-v2	Side Open Aluminum Camera Housing, PoE in (BT), Window heater, Fan, IP68, -20~65 °C , optional snap-in VAIR, Wall bracket, Sun shield
	CaMate	CA8018-1040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
	CaMate	CA8018-2040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
	CaMate	CM3218-010	IR illuminator fixed IR 10°,180m, 32w
	CaMate	CM3218-035	IR illuminator fixed IR 35°,60m, 32w
	CaMate	CM4818-1040	IR illuminator with CVA, 10°~ 40°, 100~250m, 48w
	CaMate	CM4818-180	IR illuminator with CVA, 180°, 40m, 48w
	CaMate	CM4818-2040	IR illuminator with CVA, 20°~ 40°, 120 ~ 200m, 48w
	CaMate	CM4818-4080	IR illuminator with CVA, 40°~ 80°, 60~90m, 48w
CaMate	CM4818-90120	IR illuminator with CVA, 90°~ 120°, 45~55m, 48w	



# VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
EOL Models	Bullet	IB9360-H	Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	Cube	CC8160 (HS,BLACK,CM)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), black color
	Cube	CC8160 (HS,BLACK,FEET)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), black color
	Cube	CC8160 (HS,SILVER,CM)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), silver color
	Cube	CC8160 (HS,SILVER,FEET)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), silver color
	Cube	CC8160 (W/KIT)	Indoor, 2M 180° Panoramic, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, built-in mic, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), flat mount
	Cube	CC8370-HV	Outdoor Vandal Dome, 3M 180° Panoramic, 30fps, H.264/MJPEG, f1.6mm fisheye lens, Daytime, WDR Pro, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20°C ~ 50°C/ -4°F ~ 122°F)
	Split	VC8101,(CU8161-H)	Split-type, 2M 30fps, H.264/MJPEG, f3.7 mm fixed Lens, WDR Pro, 3DNR, PoE/DC 8-36V, 5 Meters cable, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC
	Split	VC8101,(CU8163-H)	Split-type, 2M 30fps, H.264/MJPEG, f1.6 mm fixed Lens, 180° Panoramic View, WDR Pro, 3DNR, PoE/DC 8-36V, 5 Meters cable, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC
	Fisheye	FE8182	Recessed Indoor, 5M, 15fps, H.264/MJPEG, f1.05mm fisheye lens, Daytime, WDR Enhanced, PoE, built-in mic, MicroSD/SDHC/SDXC
	Corner Camera	CD8371-HNTV(METAL)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8~8mm Motorized lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14°F ~ 131°F)
	Corner Camera	CD8371-HNTV(WHITE)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8~8mm Motorized lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14°F ~ 131°F)
	Corner Camera	CD8371-HNVF2(METAL)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8mm lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14 °F ~ 131°F)
	Corner Camera	CD8371-HNVF2(WHITE)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8mm lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14 °F ~ 131°F)
	Mini Dome	FD8166A	Indoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, WDR Enhanced, 3DNR, PoE, I/O*1/0, One way audio,Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD8166A-N	Indoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, 940IR 6m, WDR Enhanced, 3DNR, PoE, One way audio, Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD816CA-HF2	Indoor Extra mini Dome, Recessed mount, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, WDR PRO,3DNR, PoE, Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD8366-V	Outdoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, 850nm IR 15M, 3DNR, PoE, I/O*1/0, One way audio, Built-in microphone, MicroSD/SDHC/SDXC
	Fixed Dome	FD8177-HT	Indoor Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
	Fixed Dome	FD8377-EHTV	Outdoor Vandal Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IK10, Working Temperature: -50°C ~ 50°C (-58°F ~ 122°F)
	Fixed Dome	FD8377-HTV	Outdoor Vandal Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IK10, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
	Fixed Dome	FD9360-H	Outdoor Fixed Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	Mobile Dome	MD8531H	Mobile Dome, 1M 30fps, H.264/MJPEG, f3.6/f4.2mm fixed Lens, WDR Pro, 3DNR, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP66, IK10, extreme weather (-25°C ~ 55°C/-13°F ~ 131°F), EN50155 T1
	Mobile Dome	MD8563-DEH	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP67, IK10, EN50155 TX
	Mobile Dome	MD8563-EH	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/f3.6mm fixed Lens, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP67, IK10, EN50155 TX
	Mobile Dome	MD8565-N	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, 940nm IR 10M, WDR Pro, 3DNR, M12, PoE, I/O*1/0, One way audio, Built-in microphone, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, EN50155 T1



## VIVOTEK America - NDAA Compliant Product List

December 14, 2022

Category	Form Factor	Model	Description
EOL Models	Rackmount NVR	NR9581,MAE,(32CH,ELABEL)	H.265, 32CH, 1 HDMI+1 VGA+ 1 DP+ 1 DVI, 1080P @ 150 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9681,MAE,(64CH,ELABEL)	H.265, 64CH, 1 HDMI+1 VGA+ 1 DP+ 1 DVI, 1080P @ 150 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9682	H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9782	H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power